

WATERMAKER

MT-50T/24h



Watermaker produces drinking water from sea water based upon the reverse osmosis membrane technique.

The capacity is 50m³/24h from seawater (25° C).

The quality of the drinking water is continuously monitored by a salinity meter.

The design is ideal for simple service and maintenance.

The unit is suitable for:

- Drilling platforms
- Offshore rigs and accommodation platforms
- Commercial vessels
- Military vessels
- Resorts, hotels and communities
- Golf courses









| MT-50T | | | |
|--|-------------|-------------------------------|------|
| Capacity (m³/24h) | 50 | Width (mm) | 1680 |
| Installed power HP (kW) (50 / 60Hz) | 15.0 / 13.2 | Depth (mm) | 1000 |
| Installed power feed pump (kW) (50 / 60Hz) | 1.5 / 1.5 | Height (mm) | 1120 |
| Raw water flow (m³/h) | 5.2 | Weight dry (kg) | 645 |
| Membranes (8") | 3 pcs | Weight (operational) wet (kg) | 730 |

The capacity is calculated with a sea water temperature at 25°C and a TDS at 35 500ppm. The treated and produced water flow will decrease with lower temperature.

Standard

- · High pressure plunger pump
- Continuoes control of the outgoing water quality, via a salinity meter and a dumping valve
- Automatic flush after each stop, via a carbon cartridge filter (neutralizing the chlorine)
- · Low pressure switch before the high pressure pump
- Feed water particle filter (5 micron)
- · Feed water pressure gauge
- · Safety valves
- · Flow meter for production flow
- All electrical equipment minimum IP54
- Low pressure switch on the suction side of the high pressure pump
- Level switch in water tank can be connected for start and stop

2

Sandfilter SA-800
Thermoplastic coated vessel
Automatic back flushing



Re-hardening filter N-80 RO Stainless steel, AISI 316L

Optional Equipment

- CIP cleaning tank
- Remote control
- Re-hardening filter in stainless steel, to increase pH
- · UV sterilizer
- Dosing equipment for chlorine, anti-scalant or chlorine removal
- · Prefiltration sand filters
- · Spare parts and consumables package
- · Portable conductivity meter and pH meter

Enwa Sweden

Importgatan 21 SE-422 46 Hisings Backa Sweden

Phone: +46 31 742 92 50 E-mail: info@enwa.se **Enwa Norway**

Nordre Kullerød 9, Postboks 1241 3205 Sandefjord Norway

Phone: +47 33 48 80 60 E-mail: post@enwa.com Enwa UK

Unit A Scotlands Industrial Estate, Coalville Leicestershire, LE67 3JJ United Kingdom Phone: +44 1530 830 354

Phone: +44 1530 830 354 E-mail: sales@enwa.co.uk